

Sans titre

AT

OK
AT+RST

OK
ets Jan 8 2013,rst cause:1, boot mode:(3,6)

load 0x40100000, len 2408, room 16
tail 8
chksum 0xe5
load 0x3ffe8000, len 776, room 0
tail 8
chksum 0x84
load 0x3ffe8310, len 632, room 0
tail 8
chksum 0xd8
csum 0xd8

2nd boot version : 1.6
SPI Speed : 40MHz
SPI Mode : DIO
SPI Flash Size & Map: 8Mbit(512KB+512KB)
jump to run user1 @ 1000
Ai-Thinker Technology Co., Ltd.
Integrated AiCloud 2.0 v0.0.0.3

ready
AT+CWLAP

ERROR
AT+CWMODE=3

OK
AT+CWLAP

+CWLAP:(3,"My ASUS crosne",-40,"70:8b:cd:9b:0f:a4",6,10,0)
+CWLAP:(4,"Livebox-DB22",-57,"8c:10:d4:ea:db:22",6,-6,0)
+CWLAP:(5,"SFR WiFi Mobile",-88,"6a:ce:7d:df:96:15",11,33,0)
+CWLAP:(4,"SFR_9610",-88,"44:ce:7d:df:96:16",11,33,0)
+CWLAP:(0,"SFR WiFi FON",-90,"6a:ce:7d:df:96:17",11,33,0)
+CWLAP:(2,"PichBox",-77,"68:a3:78:11:ab:6c",11,-2,0)

OK

AT+CWJAP="My ASUS crosne","bureau01?"

?

Sans titre

ets Jan 8 2013,rst cause:1, boot mode:(3,6)

```
load 0x40100000, len 2408, room 16
tail 8
chksum 0xe5
load 0x3ffe8000, len 776, room 0
tail 8
chksum 0x84
load 0x3ffe8310, len 632, room 0
tail 8
chksum 0xd8
csum 0xd8
```

```
2nd boot version : 1.6
  SPI Speed       : 40MHz
  SPI Mode        : DIO
  SPI Flash Size & Map: 8Mbit(512KB+512KB)
jump to run user1 @ 1000
```

```
ready
WIFI DISCONNECT
WIFI CONNECTED
WIFI GOT IP
AT+CIFSR
```

```
+CIFSR:APIP,"192.168.4.1"
+CIFSR:APMAC,"5e:cf:7f:3c:be:de"
+CIFSR:STAIP,"192.168.43.38"
+CIFSR:STAMAC,"5c:cf:7f:3c:be:de"
```

```
OK
```